


## TR-XLPE/CN/LLDPE, Type MV-90, Primary UD, 15kV 100%, 175-mils Single Conductor Filled Aluminum - Silicone Free

### DESCRIPTION

This specification covers cables that consist of Aluminum filled conductor, covered with tree-retardant cross-linked polyethylene (TR-XLPE), a concentric neutral of helically applied copper wires, and linear low density polyethylene (LLDPE) jacket with 3 extruded red stripes

### APPLICATIONS

- Suitable for underground primary power applications: direct burial or In duct.
- For wet or dry locations
- Jacket is sunlight resistant, meeting the 720-hr exposure test
- Excellent resistance to treeing
- Designed to operate continuously at a conductor temperature not exceeding
  - » 90°C for normal operations
  - » 130°C for emergency overload
  - » 250°C for short circuit



### CONSTRUCTION

<b>CONDUCTOR</b>	1350 Aluminum (filled) Class B Strand Compressed
<b>STRAND SHIELD</b>	Thermoset semi-conducting polymer ● DOW HFDA-0581
<b>INSULATION</b>	Tree-Retardant Cross-Linked Polyethylene (TR-XLPE) ● DOW HFDC-4202EC
<b>INSULATION SHIELD</b>	Thermoset semi-conducting polymer ● DOW HFDA-0693
<b>SHIELD</b>	Helically applied, annealed solid bare copper wires
<b>JACKET</b>	Linear low-density polyethylene (LLDPE)
<b>PACKAGING</b>	Non-returnable reels

### STANDARDS (Compliance)

<b>PERFORMANCE</b>	AEIC CS8 ASTM B-3 ASTM B-230 ASTM B-231 ICEA S-94-649 UL 1072
--------------------	--

### SPECIFICATIONS

Part Number	Conductor Size (AWG)	Conductor Diameter (in)	Insulation Diameter (in)	Copper Concentric Neutrals	Jacket Thickness (in)	Overall Diameter (in)	Net Weight (lbs / Mft)
E9HKT-4A6F01CAD0	4/0	0.512	0.89	11 x 14 AWG (1/3N)	0.055	1.21	720

The dimensions and weights shown are nominal and subject to industry standards. Other designs available upon request.