

TR-XLPE/CN/LLDPE, Type Primary UD (Filled)


Part Number: E9HKT-B56F01CA22

DESCRIPTION

The Medium Voltage Primary Underground Distribution (UD) cables consist of an Aluminum (filled) conductor, covered with tree-retardant cross-linked polyethylene (TR- XLPE), a concentric neutral of helically applied copper wires, moisture block and a linear low-density polyethylene (LLDPE) jacket with 3 extruded red stripes.

APPLICATION

- Suitable for underground primary power applications
- For wet or dry locations
- For direct burial or in duct
- Excellent resistance to treeing
- Jacket is sunlight-resistance
- Designed to operate
 - » 90°C for normal operations
 - » 130°C for emergency overload
 - » 250°C for short circuit



SPECIFICATIONS

Conductor	Aluminum 1350 compressed Lay stranded Class B (Filled)
Conductor	Extruded thermoset Super Smooth
Strand Shield	Semi-conducting polymer (Dow HFDA0802)
Insulation	Tree-Retardant Cross-linked Polyethylene (TR-XLPE) (Dow HFDC4202)
Insulation Shield	Carbon Black Filled Cross-Linkable Compound (Dow HFDA0693)
Neutral	Solid copper wires
Moisture Block	Powder
Jacket	Linear Low-Density Polyethylene (with water swell-able powder under jacket)

Packaging	Non-returnable reels
Performance	ASTM B-3
Compliance	ASTM B-230 ASTM B-231 ICEA S-94-649 ICEA T-31-610 (filled/water block compliant) AEIC CS8

1C 1000kcmil 61-wires Aluminum (Filled), 15kV 100% 175mils TR-XLPE, (31-wires copper x 12AWG) 1/3 reduced concentric neutral, with moisture block under LLDPE jacket

PART NUMBER AND PHYSICAL CHARACTERISTICS

Part Number	Cond Size AWG/kcmil	Cond Diameter (in.)	Insulation Diameter (in.)	Copper Concentric Neutral	Jacket Thickness (in.)	OD (in.)	Net Weight lbs./MFT
E9HKT-B56F01CA22	1000	1.106	1.530	31 x 12AWG	0.080	1.93	2,546

The dimensions and weights shown are nominal and subject to industry standards. Other designs available upon request.