

## TR-XLPE/CN/XLPE, Type Primary UD


Part Number: **E9HWT-2A6F01CA20**

### DESCRIPTION

The Medium Voltage Primary Underground Distribution (UD) cables consists of an aluminum (Filled) conductor, covered with tree-retardant cross-linked polyethylene (TR- XLPE), a concentric neutral of helically applied copper wires, moisture block and a sunlight resistant cross-linked polyethylene (XLPE) jacket with 3 extruded red stripes.

### APPLICATION

- Suitable for underground primary power applications
- For wet or dry locations
- For direct burial or in duct
- Jacket is sunlight resistant, meeting the 720-hr exposure test
- Designed to operate continuously at a conductor temperature not exceeding
  - » 105°C for normal operations
  - » 130°C for emergency overload
  - » 250°C for short circuit



### SPECIFICATIONS

<b>Conductor</b>	Aluminum 1350 compressed stranded Class B (Filled)
<b>Conductor Strand Shield</b>	Extruded thermoset Semi-conducting polymer
<b>Insulation</b>	Tree-Retardant Cross-linked Polyethylene (TR-XLPE)
<b>Neutral</b>	Concentric Neutral
<b>Moisture Block</b>	Powder
<b>Jacket</b>	Cross-linked Polyethylene (XLPE) with water swell-able powder under jacket

<b>Packaging</b>	Non-returnable reels
<b>Performance Compliance</b>	ASTM B-3, B-230, B-231 ICEA S-94-649 ICEA T-31-610 ICEA T-34-664 AEIC CS8 RUS U1 (upon request) UL 1072 (MV-105)

**1C; 2/0 AWG; 19-wires Aluminum (Filled), 15kV 100% 175-mils TR-XLPE, 1/3 reduced concentric neutral (6 x #14cu), with moisture block under XLPE jacket**

PART NUMBER AND PHYSICAL CHARACTERISTICS							
Part Number	Conductor Size (AWG/kcmil)	Cond Diameter (in.)	Copper Concentric Neutral	Insulation Diameter (in.)	Jacket Thickness (in.)	OD (in.)	Net Weight lbs./MFT
<b>Design with filled stranded aluminum</b>							
E9HWT-2A6F01CA20	2/0 AWG	.397	6 x 14Cu	.783	.055	1.09	542

The dimensions and weights shown are nominal and subject to industry standards and manufacturing tolerances. Other designs available upon request.