

EPR/CN/XLPE, Type Primary UD (Filled)


Part Number: E9JYT-A15B01CA00

DESCRIPTION

The Medium Voltage Primary Underground Distribution (UD) cables consist of a copper (filled) conductor, covered with Ethylene Propylene Rubber (EPR), a concentric neutral of helically applied copper wires, and a sunlight resistant cross-linked polyethylene (XLPE) jacket with 3 extruded red stripes.

APPLICATION

- Suitable for underground primary power applications
- For wet or dry locations
- For direct burial or in duct
- Excellent resistance to treeing
- Jacket is sunlight-resistance
- Designed to operate
 - » 105°C for normal operations
 - » 140°C for emergency overload
 - » 250°C for short circuit



SPECIFICATIONS

Conductor	Fully annealed bare copper Class B compressed strand (filled)
Conductor Strand Shield	Extruded thermoset Semi-conducting polymer
Insulation	Ethylene Propylene Rubber (EPR)
Neutral	Helically applied, annealed, solid copper bare wires
Moisture Block	Powder
Jacket	Cross-Linked Polyethylene (XLPE)

Packaging	Non-returnable reels
Performance	ASTM B-3
Compliance	ASTM B-230 ASTM B-231 ICEA S-94-649 AEIC CS8 UL 1072 (MV-105) RUS U1

1C 250AWG 37-wires Aluminum (filled), 15kV 133% 220mils EPR, (16-wires copper x 14AWG) 1/3 reduced concentric neutral, XLPE jacket

PART NUMBER AND PHYSICAL CHARACTERISTICS

Part Number	Conductor Size (AWG/kcmil)	Conductor Diameter (in.)	Copper Concentric Neutral	Insulation Diameter (in.)	Jacket Thickness (in.)	OD (in.)	Net Weight (lbs./MFT)
E9JYT-A15B01CA00	250	0.547	16 x 14AWG (1/3 RCN)	1.030	0.055	1.36	1,405

The dimensions and weights shown are nominal and subject to industry standards.