

## EPR/CN/LLDPE, Type MV-90, Primary UD, 25kV 133%, 320-MILS Single Conductor Un-Filled Aluminum -Silicone Free

### DESCRIPTION

This specification covers cables that consist of Aluminum un-filled conductor, covered with ethylene propylene rubber (EPR), a concentric neutral of helically applied copper wires, and a linear low density polyethylene (LLDPE) jacket with 3 extruded red stripes.

### APPLICATIONS

- Suitable for underground primary power applications: direct burial or in duct.
- For wet or dry locations
- Jacket is sunlight resistant, meeting the 720-hr exposure test
- Excellent resistance to treeing
- Designed to operate continuously at a conductor temperature not exceeding
  - 105°C for normal operations
  - 140°C for emergency overload
  - 250°C for short circuit

CONSTRUCTION		STANDARDS (Compliance)	
<b>CONDUCTOR</b>	1350 Aluminum (unfilled) Class B Strand Compressed	<b>PERFORMANCE</b>	AEIC CS8 ASTM B-3 ASTM B-230 ASTM B-231 ICEA S-94-649 UL 1072
<b>STRAND SHIELD</b>	Thermoset semi-conducting polymer		
<b>INSULATION</b>	Ethylene propylene rubber (EPR)		
<b>INSULATION SHIELD</b>	Thermoset semi-conducting polymer		
<b>SHIELD</b>	Helically applied, annealed, solid bare copper wires		
<b>JACKET</b>	Linear low-density polyethylene (LLDPE)		
<b>PACKAGING</b>	Non-returnable wooden reels		

SPECIFICATIONS							
Part Number	Conductor Size	Conductor Diameter (in)	Insulation Diameter (in)	Metallic Shield	Jacket Thickness (in)	Approx. Overall Diameter (in)	Approx. Net Weight (lbs/kft)
E9LPM-013F01CA00	1 AWG	0.322	0.99	13 x 14 AWG (FCN)	0.055	1.31	824
E9LPM-4A3F01CA00	4/0 AWG	0.512	1.18	32 x 14 AWG (FCN)	0.055	1.52	1,330

\*The dimensions and weights shown are nominal and subject to industry standards. Other designs available upon request.