


**TR-XLPE/CN/LLDPE, Type MV-90, Primary UD, 35kV 100%, 345MILS  
Single Conductor Filled Aluminum -Silicone Free**

**DESCRIPTION**

This specification covers cables that consist of Aluminum Filled conductor, covered with tree-retardant cross-linked polyethylene (TR-XLPE), a concentric neutral of helically applied copper wires, and a linear low density polyethylene (LLDPE) jacket with 3 extruded red stripes.

**APPLICATIONS**

- Suitable for underground primary power applications: direct burial or in duct.
- For wet or dry locations
- Jacket is sunlight resistant, meeting the 720-hr exposure test
- Excellent resistance to treeing
- Designed to operate continuously at a conductor temperature not exceeding
  - 90°C for normal operations
  - 130°C for emergency overload
  - 250°C for short circuit



CONSTRUCTION	
<b>CONDUCTOR</b>	1350 Aluminum (filled) Class B Strand Compressed
<b>STRAND SHIELD</b>	Thermoset semi-conducting polymer
<b>INSULATION</b>	Tree-retardant cross-linked polyethylene
<b>INSULATION SHIELD</b>	Thermoset semi-conducting polymer
<b>SHIELD</b>	Helically applied, annealed, solid bare
<b>JACKET</b>	Linear low-density polyethylene (LLDPE)
<b>PACKAGING</b>	Non-returnable wooden reels

STANDARDS (Compliance)	
<b>PERFORMANCE</b>	AEIC CS8 ASTM B-3 ASTM B-230 ASTM B-231 ICEA S-94-649 UL 1072

**SPECIFICATIONS**

Part Number	Conductor Size	Conductor Diameter (in)	Insulation Diameter (in)	Metallic Shield	Jacket Thickness (in)	Overall Diameter (in)	Net Weight (lbs/kft)
E9MKU-4A6F01CA00	4/0 AWG	0.512	1.23	21 x 14 AWG (2/3N)	0.055	1.57	1,162

*\*The dimensions and weights shown are nominal and subject to industry standards. Other designs available upon request.*