### **CABLE SPECIFICATION**

SPEC: LSCUS-25-CM40023 REV: 00 DATE: 04.25.25


## TR-XLPE/CN/LLDPE Power, MV-90 Type Primary UD, 35kV 100% Single Conductor Filled Aluminum - Silicone Free

#### **DESCRIPTION**

The Medium Voltage Underground Distribution (UD) cables consist of an aluminum filled conductor, covered with tree-retardant cross-linked polyethylene (TR-XLPE), a concentric neutral of helically applied copper wires, and a moisture blocked linear low-density polyethylene (LLDPE) jacket with 3 extruded red stripes.

#### **APPLICATIONS**

- Suitable for underground primary power applications: direct burial or in duct.
- For wet or dry locations.
- Jacket is sunlight resistant.
- Excellent resistance to treeing
- Designed to operate continuously at a conductor temperature not exceeding
  - » 90°C for normal operations
  - » 130°C for emergency overload
  - » 250°C for short circuit



#### **CONSTRUCTION**

CONDUCTOR	Aluminum 1350 (filled) Class B compressed strand				
STRAND SHIELD	Extruded thermoset semi-conducting polymer over the conductor				
INSULATION	Tree-retardant cross-linked polyethylene (TR-XLPE)				
INSULATION SHIELD	Extruded thermoset semi-conducting polymer over the insulation				
SHIELD	Helically applied, annealed, solid bare copper wires				
JACKET	Moisture blocked Linear low-density polyethylene (LLDPE)				
JACKET MARKING	00000 FT LS CABLE XXXKCMIL (or AWG) FS AL 1/C 35KV 133% INSUL LEVEL 420 MILS TRXLPE 'No. of Neutral' X # 'Neutral size' MB LLDPE JKT MV-90 (UL) MADE IN USA MM/DD/YYYY (LIGHTNING BOLT SYMBOL)				
PACKING	Non-returnable wood reels				

### **STANDARDS (Compliance)**

PERFORMANCE	AEIC CS8 ASTM B3 ASTM B230 ASTM B231 ICEA S-94-649 UL 1072
OTHER	OSHA



## **CABLE SPECIFICATION**

SPEC: LSCUS-25-CM40023 REV: 00 DATE: 04.25.25

# TR-XLPE/CN/LLDPE Power, MV-90 Type Primary UD, 35kV 100% Single Conductor Filled Aluminum - Silicone Free

SPECIFICATIONS									
Part Number	Conductor Size (AWG/kcmil)	Conductor Diameter (in)	Insulation Diameter (in)	Concentric Neutral (No. x AWG)	Jacket Thickness (in)	Approx. O.D (in)	Approx. Weight (lbs/kft)		
U35ATL-A2FB-1CZ-R3Z-M	1250	1.250	2.05	25 x 10 AWG (1/3N)	0.075	2.56	3,450		

The dimensions and weights shown are approximate and subject to industry standards. Other designs available upon request.